

APPENDIX A – SECONDARY REFERENCES

RULE 62-762.211, F.A.C.

July 2019

[Incorporated in subsection 62-762.211(1), F.A.C.]

2600 Blair Stone Road, MS 4525
Tallahassee, Florida 32399-2400
www.floridadep.gov



Appendix A - Secondary References for Rule 62-762.211, F.A.C

(1) The following documents are secondary references cited within the Reference Guidelines located in Rule 62-762.211, F.A.C., and are available directly from the source. These secondary references are used in the primary reference guidelines located in Rule 62-762.211, F.A.C., and have insufficient information how to obtain these references. All other secondary references can be obtained through the primary reference documents located in Rule 62-762.211, F.A.C.

(2) Each document or part thereof is adopted and incorporated by reference as a guideline only to the extent that it is specifically referenced within the Reference Guidelines located in Rule 62-762.211, F.A.C. To the extent that the provisions contained in the following secondary reference guidelines conflict with Chapter 62-762, F.A.C., the Department's requirements as stated in Chapter 62-762, F.A.C., shall control.

(a) American Petroleum Institute (API), 1220 L Street, N.W. Washington, D.C. 20005, (202) 682-8000, or at <http://www.api.org/>:

1. *Specification for Field Welded Tanks for Storage of Production Liquids*, API Spec 12D, Twelfth Edition, available at https://www.techstreet.com/standards/api-spec-12d?product_id=1983654, or at the address above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.;
2. *Specification for Shop Welded Tanks for Storage of Production Liquids*, API Spec 12F, Thirteenth Edition, available at https://www.techstreet.com/standards/api-spec-12f?product_id=2032931, or at the address above. This secondary reference is located in reference guidelines STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C., and STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.;
3. *Recommended Practice for Setting, Maintenance, Inspection, Operation and Repair of Tanks in Production Service*, API RP 12R1 (R2008), Includes Addendum 1 (2017), available at https://www.techstreet.com/standards/api-rp-12r1-r2008?product_id=8299, or the address listed above. This secondary reference is located in reference guidelines STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C., and STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.;
4. *Suggested Procedure for Development of Spill Prevention Control and Countermeasure Plans*, API Bulletin D16, Fifth Edition, 2011, available at https://www.techstreet.com/standards/api-bull-d16?product_id=1784246, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.;
5. *A Survey of Diked-Area Liner Use at Aboveground Storage Tank Facilities*, API Publ 341, February 1998, available at https://www.techstreet.com/standards/api-publ-341?product_id=55744, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.;
6. *Inspection of Existing Atmospheric and Low-pressure Storage Tanks*, API RP 575, Third Edition, 2014, available at <https://www.techstreet.com/searches/23987001>, or the address listed above. This secondary reference is located in reference guidelines STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C., and STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.;
7. *Loading and Unloading of MC 306 / DOT 406 Cargo Tank Motor Vehicles*, API RP 1007, March 2001, available at <http://www.techstreet.com/api/searches/8090261>, or the address listed above. This secondary reference is located in reference guideline API Recommended Practice 1637 under subparagraph 62-762.211(2)(b)10., F.A.C.;
8. *Bulk Liquid Stock Control at Retail Outlets*, API RP 1621 (R2012), 5th Edition, available at <http://www.techstreet.com/products/14616>, or the address listed above. This secondary reference is located in reference guideline STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.;
9. *Requirements for Safe Entry and Cleaning of Petroleum Storage Tanks*, API Standard 2015, 2018, available at https://global.ihs.com/doc_detail.cfm?document_name=API%20STD%202015&item_s_key=00010492, or at the address listed above. This secondary reference is located in reference guidelines STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C. and STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.; and,
10. *Design, Construction, Operation, Maintenance, and Inspection of Terminal & Tank Facilities*, API RP 2610, (R2010), 2nd Edition, available at <http://www.techstreet.com/products/1218646>, or the address listed above. This secondary reference is located in reference guideline STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.

(b) American Welding Society, 8669 NW 36 Street, # 130, Miami, Florida 33166-6672, or at <https://www.aws.org/>. Structural Welding Code-Steel, D1.1/D1.1M:2015, available at <https://pubs.aws.org/p/1650/d11d11m2015-2nd->

printing-structural-welding-code-steel, or the address above. This secondary reference is located in reference guideline STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.

(c) Ansuini, F.J., Dimond, J.R., *Factors Affecting the Accuracy of Reference Electrodes*, MP 33, 11 (1994): pp. 14-17. This secondary reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.

(d) ASME International (founded as the American Society of Mechanical Engineers), 22 Law Drive, Box 2900, Fairfield, New Jersey 07007-2900, (800) 843-2763, or at <http://www.asme.org/>:

1. *Pipe Flanges and Flanged Fittings: NPS 1/2 through NPS 24 Metric/Inch Standard*, ASME B16.5, 2013, available at <https://www.asme.org/products/codes-standards/b165-2013-pipe-flanges-flanged-fittings-nps-12>, or the address listed above. This secondary reference is located in reference guideline UL 142, in subparagraph 62-762.211(2)(m)1., F.A.C.;

2. *Forged Fittings, Socket-Welding and Threaded*, ASME B16.11, 2011, available at <https://www.asme.org/products/codes-standards/b1611-2011-forged-fittings-socketwelding-threaded>, or the address listed above. This secondary reference is located in reference guideline UL 142, in subparagraph 62-762.211(2)(m)1., F.A.C.; and,

3. *Boiler and Pressure Vessel Code*, 2019 Edition, Section IX, *Welding, Brazing, and Fusing Qualifications*, available at <https://www.asme.org/products/codes-standards/bpvcix-2019-bpvc-section-ixwelding-brazing-fusing>, or the address listed above. This secondary reference is located in reference guideline STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.

(e) ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, Pennsylvania, 19428-2959, (877) 909-2786, or at <http://www.astm.org/>:

1. *Standard Specification for Carbon Structural Steel*, ASTM A36/A36M, 2014, available at <http://www.astm.org/Standards/A36.htm>, or the address listed above. This secondary reference is located in reference guidelines STI F001, in subparagraph 62-762.211(2)(l)1., F.A.C.; STI F941 in subparagraph 62-762.211(2)(l)4., F.A.C.; and UL 142, in subparagraph 62-762.211(2)(m)1., F.A.C.;

2. *Standard Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip*, ASTM A167-99 (2009), withdrawn but still available at <http://www.astm.org/DATABASE.CART/HISTORICAL/A167-99.htm>, or the address listed above. This secondary reference is located in reference guideline UL 142, in subparagraph 62-762.211(2)(m)1., F.A.C.;

3. *Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications*, ASTM 240/240M-15a, 2015, available at <http://www.astm.org/Standards/A240.htm>, or the address listed above. This secondary reference is located in reference guideline UL 142, in subparagraph 62-762.211(2)(m)1., F.A.C.;

4. *Standard Specification for Steel, Carbon (0.15 Maximum, Percent), Hot-Rolled Sheet and Strip Commercial (Withdrawn 2000)*, A569/A569M, Replaced by A1011/A1011M, 2014, located in Appendix (2)(c)7., F.A.C., or available at <http://www.astm.org/Standards/A1011.htm>. This secondary reference is located in reference guidelines STI F001, in subparagraph 62-762.211(2)(l)1., F.A.C., and STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.;

5. *Standard Specification for Steel, Sheet and Strip, Heavy-Thickness Coils, Hot-Rolled, Alloy, Carbon, Structural, High-Strength Low-Alloy, and High-Strength Low-Alloy with Improved Formability, General Requirements for*, ASTM A635/A635M-14, 2014, available at <http://www.astm.org/Standards/A635.htm>, or the address listed above. This secondary reference is located in reference guidelines STI F001, in subparagraph 62-762.211(2)(l)1., F.A.C.; STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.; and UL 142, in subparagraph 62-762.211(2)(m)1., F.A.C.;

6. *Standard Specification for Threaded Couplings, Steel, Black or Zinc-Coated (Galvanized) Welded or Seamless, for Use in Steel Pipe Joints*, ASTM A865/A865M – 06(2012), available at <http://www.astm.org/Standards/A865.htm>, or the address listed above. This secondary reference is located in reference guideline UL 142, in subparagraph 62-762.211(2)(m)1., F.A.C.;

7. *Standard Specification for Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy, High-Strength Low-Alloy with Improved Formability, and Ultra-High Strength*, ASTM A1011/A1011M, 2014, available at <http://www.astm.org/Standards/A1011.htm>, or the address listed above. This secondary reference is located in reference guidelines STI F001, in subparagraph 62-762.211(2)(l)1., F.A.C.; STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.; and UL 142, in subparagraph 62-762.211(2)(m)1., F.A.C.;

8. *Standard Specification for Cast and Wrought Galvanic Zinc Anodes*, ASTM B418 - 16a, 2016, available at <https://www.astm.org/Standards/B418.htm>, or the address listed above. This secondary reference is located in reference guideline GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C.;
9. *Standard Specification for Aggregate for Masonry Mortar*, ASTM C144 – 18, 2018, available at <https://www.astm.org/Standards/C144.htm>, or at the address listed above. This secondary reference is located in reference guideline GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C.;
10. *Standard Specification for Standard Sand*, ASTM C778 – 17, 2017, available at <https://www.astm.org/Standards/C778.htm>, or the address listed above. This secondary reference is located in reference guideline GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C.;
11. *Standard Test Method for Rubber Property—Effect of Liquids*, ASTM D471-12a, 2012, available at <http://www.astm.org/Standards/D471.htm>, or the address listed above. This secondary reference is located in reference guideline UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
12. *Standard Test Methods for Density and Specific Gravity (Relative Density) of Plastics by Displacement*, ASTM D792-13, 2013, available at <http://www.astm.org/Standards/D792.htm>, or the address listed above. This secondary reference is located in reference guideline GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C.;
13. *Standard Test Method for Tear Resistance (Graves Tear) of Plastic Film and Sheeting*, ASTM D1004-13, 2013, available at <http://www.astm.org/Standards/D1004.htm>, or the address listed above. This secondary reference is located in reference guideline GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C.;
14. *Standard Specification for Reagent Water*, ASTM D1193-06, (Reapproved 2011), available at <http://www.astm.org/Standards/D1193.htm>, or the address listed above. This secondary reference is located in reference guideline UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
15. *Standard Test Method for Melt Flow Rates of Thermoplastics by Extrusion Plastometer*, ASTM D1238-13. 2013, available at <http://www.astm.org/Standards/D1238.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
16. *Standard Test Method for Density of Plastics by the Density-Gradient Technique*, ASTM D1505-10, 2010, available at <http://www.astm.org/Standards/D1505.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
17. *Standard Test Method for Carbon Black Content in Olefin Plastics*, ASTM 1603-14, 2014, available at <http://www.astm.org/Standards/D1603.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
18. *Standard Test Method for Cyclic Pressure Strength of Reinforced, Thermosetting Plastic Pipe*, ASTM D2143-00, (Reapproved 2010), available at <http://www.astm.org/Standards/D2143.htm>, or the address listed above. This secondary reference is located in reference guideline UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
19. *Standard Test Method for Apparent Hoop Tensile Strength of Plastic or Reinforced Plastic Pipe*, ASTM D2290-12, 2012, available at <http://www.astm.org/Standards/D2290.htm>, or the address listed above. This secondary reference is located in reference guideline UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
20. *Standard Test Method for Determination of External Loading Characteristics of Plastic Pipe by Parallel-Plate Loading*, ASTM D2412-11, 2011, available at <http://www.astm.org/Standards/D2412.htm>, or the address listed above. This secondary reference is located in reference guideline UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
21. *Standard Specification for Reinforced Epoxy Resin Gas Pressure Pipe and Fittings*, ASTM D2517-06, (Reapproved 2011), available at <http://www.astm.org/Standards/D2517.htm>, or the address listed above. This secondary reference is located in reference guideline UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
22. *Standard Test Method for Oxidative-Induction Time of Polyolefins by Differential Scanning Calorimetry*, ASTM D3895-14, 2014, available at <http://www.astm.org/Standards/D3895.htm>, or the address listed above. This secondary reference is located in references GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and guidelines UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
23. *Standard Test Method for Determination of Carbon Black Content in Polyethylene Compounds By the Muffle-Furnace Technique*, ASTM D4218-96(2008), available at <http://www.astm.org/Standards/D4218.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;
24. *Standard Test Method for Index Puncture Resistance of Geomembranes and Related Products*, ASTM

D4833/D4833M-07(2013)e1, available at <http://www.astm.org/Standards/D4833.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

25. *Standard Test Method for Measuring the Nominal Thickness of Geosynthetics*, ASTM D5199-12, 2012, available at <http://www.astm.org/Standards/D5199.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

26. *Standard Test Method for Evaluation of Stress Crack Resistance of Polyolefin Geomembranes Using Notched Constant Tensile Load Test*, ASTM D5397-07(2012), available at <http://www.astm.org/Standards/D5397.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

27. *Standard Test Method for Microscopic Evaluation of the Dispersion of Carbon Black in Polyolefin Geosynthetics*, ASTM D5596-03(2009), available at <http://www.astm.org/Standards/D5596.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

28. *Standard Practice for Air-Oven Aging of Polyolefin Geomembranes*, ASTM D5721-08(2013), available at <http://www.astm.org/Standards/D5721.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

29. *Standard Test Method for Oxidative Induction Time of Polyolefin Geosynthetics by High-Pressure Differential Scanning Calorimetry*, ASTM D5885/D5885M-15, 2015, available at <http://www.astm.org/Standards/D5885.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

30. *Standard Test Method for Measuring Core Thickness of Textured Geomembranes*, ASTM D5994/D5994M-10(2015)e1, available at <http://www.astm.org/Standards/D5994.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

31. *Standard Test Method for Rubber—Compositional Analysis by Thermogravimetry (TGA)*, ASTM D6370-99(2014), available at <http://www.astm.org/Standards/D6370.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

32. *Standard Test Method for Determining Tensile Properties of Nonreinforced Polyethylene and Nonreinforced Flexible Polypropylene Geomembranes*, ASTM D6693/D6693M-04(2015)e1, available at <http://www.astm.org/Standards/D6693.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

33. *Standard Test Method for Effect of Exposure of Unreinforced Polyolefin Geomembrane Using Fluorescent UV Condensation Apparatus*, ASTM D7238-06(2012), available at <http://www.astm.org/Standards/D7238.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.;

34. *Standard Test Method for Measuring Asperity Height of Textured Geomembranes*, ASTM D7466/D7466M-10(2015)e1, available at <http://www.astm.org/Standards/D7466.htm>, or the address listed above. This secondary reference is located in reference guidelines GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C., and UL 971, in subparagraph 62-762.211(2)(m)2., F.A.C.; and,

35. *Standard Test Method for Field Measurement of Soil Resistivity Using the Wenner Four-Electrode Method*, ASTM G57-06 (2012), available at <https://www.astm.org/Standards/G57.htm>, or the address listed above. This secondary reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.

(f) Barlo, T.J., Berry, W.E., *An Assessment of Current Criteria for Cathodic Protection of Buried Pipelines*, MP 23 9 (1994): pp.14-17. This secondary reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.

(g) Barnes, H.E., *Electrical Survey Detects Underground Rock*, Pipeline Industry, April 1959. This secondary

reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.

(h) Convault Owner's Manual, available at <http://www.convault.com/Content/pdfs/owners.pdf>. See Maintenance Manual Section. This secondary reference is located in STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.

(i) Geosynthetic Institute, 475 Kedron Avenue, Folsom, Pennsylvania 19033-1208, (610) 522-8440, or at <http://www.geosynthetic-institute.org/>; *The Stress Crack Resistance of HDPE Geomembrane Sheet*, GRI Guide GM10, July 23, 2015, Revision 4, available at <http://www.geosynthetic-institute.org/grispecs/gm10.pdf>. This secondary reference is located in reference guideline GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C.

(j) International Fire Code® (IFC®), 500 New Jersey Avenue, NW, 6th Floor, Washington, DC 20001, (888) 422-7233, or at <https://www.iccsafe.org/products-and-services/i-codes/2018-i-codes/ifc/>. *International Fire Code®*, 2018. This secondary reference is located in reference guidelines PEI/RP 100-17, in subparagraph 62-762.211(2)(j)1., F.A.C., and STI F001, subparagraph 62-762.211(2)(l)1., F.A.C., STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C., and STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.

(k) NACE International, 1440 South Creek Drive, Houston, Texas 77084-4906, (800)797-6223, or at <http://www.nace.org/>:

1. *Prediction of Shallow and Deep Groundbed Resistance Using Electro-Magnetic Conductivity Measurement Techniques*, CORROSION/87, paper 87310. This secondary reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.;
2. *Control of External Corrosion on Underground or Submerged Metallic Piping Systems-HD198*, NACE Standard RP-01-69-HD1983-SG, available at <https://store.nace.org/rp-01-69-control-of-external-corrosion-on-underground-or-submerged-metallic-piping-systems-hd1983>. This secondary reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.;
3. *Design, Installation, Operation, and Maintenance of Impressed Current Deep Anode Beds*, SP0572-2007-SG (formerly RP0572), available at <https://store.nace.org/sp0572-2007-formerly-rp0572->, or the address listed above. This secondary reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.; and,
4. *Measurement Techniques Related to Criteria for Cathodic Protection of Underground Storage Tank Systems*, TM0101-2012, available at <https://store.nace.org/measurement-techniques-related-to-criteria-for-cathodic-protection>, or the address listed above. This secondary reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.

(l) National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, Massachusetts 02169, (617) 770-3000, or at www.nfpa.org/.

1. *Fire Code*, NFPA 1, 2015, available at <http://www.nfpa.org/codes-and-standards/document-information-pages?mode=code&code=1>, or the address listed above. This secondary reference is located in reference guidelines PEI/RP 100-17, in subparagraph 62-762.211(2)(j)1., F.A.C., STI F001, subparagraph 62-762.211(2)(l)1., F.A.C., and STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.;
2. *National Electrical Code®*, NFPA 70, 2017, available at <https://www.nfpa.org/codes-and-standards/all-codes-and-standards/list-of-codes-and-standards/detail?code=70>, or the address listed above. This secondary reference is located in reference guideline in PEI/RP100-17, in subparagraph 62-762.211(2)(j)1., F.A.C., and PEI/RP1200-17, in subparagraph 62-762.211(2)(j)3., F.A.C.;
3. *Recommended Practice on Static Electricity*, NFPA 77, 2019, available at <https://www.nfpa.org/codes-and-standards/all-codes-and-standards/list-of-codes-and-standards/detail?code=77>, or at the address above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.;
4. *Standard for the Safeguarding of Tanks and Containers for Entry, Cleaning, or Repair*, NFPA 326, 2020, available at <https://www.nfpa.org/codes-and-standards/all-codes-and-standards/list-of-codes-and-standards/detail?code=326>, or at the address above. This secondary reference is located in reference guidelines STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C., and STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.; and,
5. *Standard for the Installation of Lightning Protection Systems*, NFPA 780, 2014, available at <http://www.nfpa.org/codes-and-standards/document-information-pages?mode=code&code=780>. This secondary

reference is located in reference guideline STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.

(m) Occupational Safety and Health Administration (OSHA), 200 Constitution Ave NW, Washington, DC 20210, (800) 321-6742, or at <https://www.osha.gov/>. *Gear Certification*, 29 CFR 1919, available at https://www.ecfr.gov/cgi-bin/text-idx?SID=e20fdd255d0e5980dbf2f5c5f966ca65&mc=true&tpl=/ecfrbrowse/Title29/29cfr1919_main_02.tpl. This secondary reference is located in reference guideline PEI/RP1200-17, in subparagraph 62-762.211(2)(j)3., F.A.C.

(n) Petroleum Equipment Institute (PEI), Post Office Box 2380, Tulsa, Oklahoma 74101-2380, (918)494-9696, or www.pei.org/:

1. *Recommended Practices for Installation and Testing of Vapor Recovery Systems at Vehicle Fueling Sites*, PEI/RP 300, 2019, available at <https://www.pei.org/rp300>, or the address listed above. This secondary reference is located in reference guidelines PEI/RP100-17, in subparagraph 62-762.211(2)(j)1., and PEI/RP1200-17, in subparagraph 62-762.211(2)(j)3., F.A.C.;

2. *Recommended Practices for Inspection and Maintenance of Motor Fuel Dispensing Equipment*, PEI/RP500, 2011, available at <https://www.pei.org/rp500>, or the address listed above. This secondary reference is located in reference guideline PEI/RP1200-17, in subparagraph 62-762.211(2)(j)3., F.A.C.; and,

3. *Recommended Practices for the Inspection and Maintenance of UST Systems*, PEI/RP900, 2017, available at <https://www.pei.org/rp900>, or the address listed above. This secondary reference is located in reference guideline PEI/RP1200-17, in subparagraph 62-762.211(2)(j)3., F.A.C.

(o) Steel Tank Institute (STI), 944 Donata Court, Lake Zurich, Illinois 60047, (847) 438-8265, or at <https://www.steeltank.com/>:

1. *Storage Tank Maintenance Standard*, STI R111, 2015, available at <http://www.steeltank.com/Publications/STISPFASStore/ProductDetail/tabid/502/rvdsfpid/storage-tank-maintenance-standard-r111-308/Default.aspx>. This secondary reference is located in reference guidelines STI F001, in subparagraph 62-762.211(2)(l)1., F.A.C.; STI F011, in subparagraph 62-762.211(2)(l)2., F.A.C.; STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.; STI R912, in subparagraph 62-762.211(2)(l)6., F.A.C.; and,

2. *RP for External Corrosion Protection of Shop Fabricated Aboveground Storage Tank Floors*, STI R893, Revised 2006, available at <http://www.steeltank.com/Publications/STISPFASStore/ProductDetail/tabid/502/rvdsfpid/rp-for-external-corrosion-protection-of-shop-fabricated-aboveground-storage-tank-floors-r893-212/rvdsfcetid/shop-sfabricated-atmospheric-tank-documents-3/Default.aspx>. This secondary reference is located in reference guidelines STI F011, in subparagraph 62-762.211(2)(l)2., F.A.C., STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C., and STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.

(p) Underwriters' Laboratory of Canada (ULC), 333 Pflingsten Road, Northbrook, IL 60062-2096, (847) 272-8800, or at <http://canada.ul.com/ulcstandards/>:

1. *Standard for Shop Fabricated Steel Aboveground Tanks for Flammable and Combustible Liquids*, ULC S601-14, 5th Edition, available at http://canada.ul.com/wp-content/uploads/sites/11/2014/06/Standards_Bulletin_2014-09_S601-14_en.pdf. This secondary reference is located in reference guidelines STI F001, subparagraph 62-762.211(2)(l)1., F.A.C.; STI F011, in subparagraph 62-762.211(2)(l)2., F.A.C.; and STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.; and,

2. *Standard for Aboveground Protected Tank Assemblies for Flammable and Combustible Liquids*, ULC S655-98, available at <https://www.scc.ca/en/standardsdb/standards/7055>. This secondary reference is located in reference guideline STI F011, in subparagraph 62-762.211(2)(l)2., F.A.C.; and STI F941, in subparagraph 62-762.211(2)(l)4., F.A.C.

(q) U.S. Department of Labor, Occupational Safety and Health Administration (OSHA), 200 Constitution Ave NW, Washington, DC 20210 or at <https://www.osha.gov/>:

1. *Permit-Required Confined Spaces*, 29 CFR Part 1910.146, available at https://www.osha.gov/Reduction_Act/CON-SPA3.html. This secondary reference is located in reference guideline STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.;

2. *The Control of Hazardous Energy (Lockout Tagout)*, OSHA 3120, 2002 (Revised), 29 CFR Part 1910.147, available at <https://www.osha.gov/Publications/3120.html>, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C., and STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.;

3. *The Control of Hazardous Energy (Lockout/Tagout)*, 29 CFR Part 1910.147, available at <https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.147>, or the address listed above. This secondary reference is located in reference guideline in STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.;

4. *Electrical Lockout/Tagout*, 29 CFR Part 1910.333, available at <https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.333>, or the address listed above. This secondary reference is located in reference guidelines STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C., and STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.; and,

5. *Confined Space in Construction*, 29 CFR Part 1926.1200, available at <https://www.osha.gov/laws-regs/regulations/standardnumber/1926/1926SubpartAA> or the address listed above. This secondary reference is located in reference guideline STI SP031, in subparagraph 62-762.211(2)(l)8., F.A.C.

(r) U.S. Department of Transportation, 1200 New Jersey Avenue, SE, Washington, Dc 20590, or at <https://www.transportation.gov/>:

1. *Reuse, reconditioning and remanufacture of packagings*, 49 CFR 173.28, available at <https://www.gpo.gov/fdsys/pkg/CFR-2012-title49-vol2/pdf/CFR-2012-title49-vol2-sec173-28.pdf>, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.;

2. *Testing of IBC's*, 178-49 CFR Subpart O, available at <https://www.ecfr.gov/cgi-bin/text-idx?SID=e55442903e1b1f187d4dfcb92858adee&mc=true&node=sp49.3.178.o&rgn=div6>, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.;

3. *Testing and Certification of IBCs*, 49 CFR 178.803, available at https://www.ecfr.gov/cgi-bin/text-idx?SID=e55442903e1b1f187d4dfcb92858adee&mc=true&node=sp49.3.178.o&rgn=div6#se49.3.178_1803, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.; and,

4. *Requirements for periodic testing, inspection and repair of portable tanks*, 49 CFR 180.605, available at https://www.ecfr.gov/cgi-bin/text-idx?SID=589abf553c7a4b7ca905f647790c0afc&mc=true&node=se49.3.180_1605&rgn=div8, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.

(s) U.S. Environmental Protection Agency, 1200 Pennsylvania Avenue, N.W., Washington, DC 20460, or at <https://www.epa.gov/>:

1. Technical Guidance Document: *Quality Assurance And Quality Control For Waste Containment Facilities*, EPA/600/R-93/182, September 1993, available at https://cfpub.epa.gov/si/si_public_record_report.cfm?Lab=NRMRL&dirEntryId=124793. This secondary reference is located in reference guideline GRI Test Method GM13, in subparagraph 62-762.211(2)(f), F.A.C.;

2. *Oil Pollution Prevention* 40 CFR Part 112, available at https://www.ecfr.gov/cgi-bin/text-idx?tpl=/ecfrbrowse/Title40/40cfr112_main_02.tpl, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.; and,

3. *Musts for USTs*, EPA 510-K-15-001, November 2015, available at <https://www.epa.gov/ust/musts-usts>, or the address listed above. This secondary reference is located in reference guideline STI SP001, in subparagraph 62-762.211(2)(l)7., F.A.C.

(t) von Baeckmann, W., Schwenk, W., Prinz, W., *Handbook of Corrosion Protection*, 3rd Edition (Burlington, MA: Elsevier, 1997), p. 72. This secondary reference is located in reference guideline NACE Standard SP0193-2016-SG (formerly RP0193-2001), 2016 Edition, in subparagraph 62-762.211(2)(g)1., F.A.C.